

DRY BOX

| TYPE | WEIGHT | | CAPACITY | EXTERNAL SIZE (MM) | | | INTERNAL SIZE (MM) | | | DOOR OPENING | |
|-------|-------------|-----------|----------|--------------------|-------|--------|--------------------|-------|--------|--------------|--------|
| | Payload kg | Tare | | Length | Width | Height | Length | Width | Height | Width | Height |
| 20'DC | 21700-28240 | 2210-2400 | 33.3 | 6058 | 2438 | 2591 | 5900 | 2345 | 2400 | 2335 | 2290 |
| 40'DC | 26740-26850 | 3630-3740 | 67.7 | 12192 | 2438 | 2591 | 12030 | 2345 | 2400 | 2335 | 2290 |
| 40'HC | 26580-26600 | 3880-3900 | 76.5 | 12192 | 2438 | 2896 | 12030 | 2350 | 2690 | 2335 | 2595 |

FLAT RACK

| TYPE | WEIGHT | | CAPACITY | EXTERNAL SIZE (MM) | | | INTERNAL SIZE (MM) | | | LEVEL LOAD | |
|-------|-------------|-----------|----------|--------------------|-------|--------|--------------------|-------|-----------|---------------|---------------------|
| | Payload kg | Tare | | Length | Width | Height | Length | Width | Height | Lateral leng. | Width between sides |
| 20'FR | 17859-30150 | 2350-2500 | NIL | 6058 | 2438 | 2591 | 5900 | 2400 | 2270-2285 | 5530-5700 | 2230-2250 |
| 40'FR | 40100 | 4900 | NIL | 12192 | 2438 | 2591 | 12150 | 2400 | 2035 | 11835 | 2230-2240 |

OPEN TOP

| TYPE | WEIGHT | | CAPACITY | EXTERNAL SIZE (MM) | | | INTERNAL SIZE (MM) | | | DOOR OPENING | | ROOF OPENING | |
|-------|-------------|-----------|-----------|--------------------|-------|--------|--------------------|-----------|--------|--------------|-----------|--------------|-----------|
| | Payload kg | Tare | | Length | Width | Height | Length | Width | Height | Width | Height | Length | Width |
| 20'OT | 21770-28230 | 2230-2250 | 31.8-32.9 | 6058 | 2438 | 2591 | 5900 | 2330-2340 | 2380 | 2330 | 2220-2250 | 5540-5760 | 2190-2210 |
| 40'OT | 26830 | 3650 | 67.1 | 12192 | 2438 | 2591 | 12045 | 2340 | 2380 | 2235 | 2255 | 11890 | 2185-2210 |

REFER CONTAINER (Controlled temperature - 25/+25°C)

| TYPE | WEIGHT | | CAPACITY | EXTERNAL SIZE (MM) | | | INTERNAL SIZE (MM) | | | DOOR OPENING | | VOLTAGE/Hz |
|-------|-------------|-----------|-----------|--------------------|-------|--------|--------------------|-----------|-----------|--------------|-----------|-----------------------------|
| | Payload kg | Tare | | Length | Width | Height | Length | Width | Height | Width | Height | 3-Phase |
| 20'RC | 17090-27280 | 2850-3500 | 26.2-28.3 | 6058 | 2438 | 2591 | 5480-5500 | 2230-2285 | 2135-2255 | 2165-2285 | 2160-2210 | 180-220V & 380-440V 50/60Hz |
| 40'RC | 25080-25980 | 4500-5400 | 57.5-58.7 | 12192 | 2438 | 2591 | 11235-11575 | 2240-2285 | 2175-2250 | 2240-2280 | 2200 | 380/440V, 50/60Hz |
| 40'HR | 25780-29250 | 4700-5200 | 66.7-68 | 12192 | 2438 | 2895 | 11575 | 2280-2550 | 2525-2550 | 2280-2290 | 2435 | 1380/440V, 50/60Hz |

TANK CONTAINER

| TYPE | WEIGHT | | CAPACITY | EXTERNAL SIZE (MM) | | |
|-------|------------|------|----------|--------------------|-------|--------|
| | Payload kg | Tare | | Length | Width | Height |
| 20'RC | 30480 | 3159 | 24000 | 6058 | 2438 | 2591 |

HARD TOP

| TYPE | WEIGHT | | CAPACITY | EXTERNAL SIZE (MM) | | | INTERNAL SIZE (MM) | | | DOOR OPENING | |
|-------|------------|------|----------|--------------------|-------|--------|--------------------|-------|--------|--------------|--------|
| | Payload kg | Tare | | Length | Width | Height | Length | Width | Height | Width | Height |
| 20' | 27890 | 2590 | 32.8 | X | X | X | 5886 | 2342 | 2375 | 2336 | 2280 |
| 40' | 25780 | 4700 | 67.2 | X | X | X | 12020 | 2342 | 2388 | 2336 | 1896 |
| 40'HC | 25780 | 4700 | 75.8 | X | X | X | 12020 | 2342 | 2693 | 2336 | 1896 |